

Features

- Operates via battery, plug-in AC power, or Hybrid Energy System (each sold separately)
- Design-forward aesthetic for commercial bathroom spaces
- Below-counter valving reduces the faucet footprint and provides easier service
- 0.5 gpm (1.9 lpm) maximum flow rate with vandal-resistant outlet
- On-demand usage with 30-second max. continual run cycle to prevent vandalism and save water
- Pair with select KOHLER® soap dispensers and single or two-hole escutcheons for an easy retrofit
- Includes spout and control box assemblies, and standard mounting hardware
- Less drain
- Concealed mechanical mixer sold separately
- Complies with the Safe Drinking Water Act (SDWA)

Material

- Premium material construction for durability and reliability

Installation

- Single-hole mounting

Required Products/Accessories

K-13480-A AC Single Supply

or

K-13481-A Multi-Outlet Power Supply

or

K-28520 High-efficiency battery pack for commercial touchless sensor faucets

or

K-36264 DC-powered battery pack for commercial touchless faucets

Recommended Products/Accessories

K-13480 AC Single Supply

K-13481 Multi-Outlet Power Supply

K-99799 Thermostatic Tempering Valve

K-24154 Mechanical mixing valve

Optional Products/Accessories

K-38166 8" two-hole escutcheon plate for Insight™ and Kinesis® lavatory faucets and soap dispensers

K-38167 4" two-hole escutcheon plate for Insight™ and Kinesis® lavatory faucets and soap dispensers

K-38168 8" two-hole escutcheon plate for Insight™ and Kinesis® lavatory faucets and soap dispensers

K-38169 4" two-hole escutcheon plate for Insight™ and Kinesis® lavatory faucets and soap dispensers



ADA

CSA B651

OBC

Codes/Standards

ASME A112.18.1/CSA B125.1

NSF/ANSI/CAN 61

NSF/ANSI/CAN 372

DOE - Energy Policy Act 1992

California Energy Commission (CEC)

ADA

ICC/ANSI A117.1

CSA B651

OBC

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description

	CP	Polished Chrome
---	----	-----------------

