

Features

- 36" (914 mm) minimum base cabinet width
- Single bowl
- 5" (127 mm) depth
- Rear offset drain increases workspace in the sink and storage space underneath
- No faucet holes; requires wall- or deck-mount faucet
- Matte finish offers rich, dimensional color
- Includes sink rack
- Sink drain and strainer sold separately

Material

- KOHLER Neoroc composite material is thermal shock-resistant and heat-resistant to 750°F (399°C)
- Color-dense Neoroc material helps to minimize the appearance of scratches and stains

Installation

- Undermount

Recommended Products/Accessories


- K-8801 Sink drain and strainer with tailpiece
- K-8799 Sink drain and strainer basket
- K-23726 Drain treatment
- K-23730 Neoroc® cleaner

Optional Products/Accessories

- K-11352 Disposal Flange with Stopper
- K-9000 P-Trap

Included Components

- K-6639 Sink racks for 36" Whitehaven®



ADA

Codes/Standards







CSA B45.5/IAPMO Z124
ADA
ICC/ANSI A117.1


KOHLER® Neoroc® Sinks Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	CM6	Matte White
	CM7	Matte Graphite
	CM1	Matte Black
	CM2	Matte Brown
	CM3	Matte Taupe
	CM4	Matte Grey



Technical Information

All product dimensions are nominal.

Basin configuration: Single Bowl
Min. base cabinet width: 36" (914 mm)

Bowl area (Only): Length: 30-1/2" (775 mm)
Width: 15-5/16" (389 mm)
Bowl depth: 5" (127 mm)
Water depth: 5" (127 mm)

Drain hole: 3-7/8" (98 mm)

Template: Undermount, 1256394-7, required, included

Notes

Install this product according to the installation instructions.

NOTICE: Countertop manufacturer or cutter must use the cut-out template provided with the product, or a current one provided by Kohler Co. (call 1-800-4-KOHLER). Kohler Co. is not responsible for cutout errors when the incorrect cut-out template is used.

ADA compliant when installed to the specific requirements of these regulations.