

Features

- Digital control with easy-to-read icons and configurable touch screen
- Control temperature, flow, and up to six shower outlets from a simple, intuitive interface
- Turn the large KOHLER® dial for easy temperature and flow rate adjustment
- Nine user-definable presets let you save your favorite shower settings
- Use with the KOHLER Konnect® app to unlock additional Anthem system features, Kohler-developed experiences, and system updates
- System warm-up and pause feature
- Includes optional flow restrictor, limiting total flow to 1.75 gpm (6.6 lpm), for installations where water conservation or CEC compliance is desired
- Features multiple language options
- Connect up to two controls within your digital shower system
- Requires an Anthem digital thermostatic valve (K-28209, K-28210, K-28211 or K-28212); sold separately
- Pair with optional Anthem remote on/off button; sold separately



Codes/Standards

UL 1951
CSA C22.2 No. 68

KOHLER® Electronic Faucets, Valves, and Controls Five-Year Limited Warranty

See website for detailed warranty information.

Material

- Premium material construction for durability and reliability

Installation

- After digital control is connected to valve and power source, follow on-screen prompts for easy setup; no Internet needed
- Wall-mount

Required Products/Accessories

K-28209 Two-port digital thermostatic valve

or

K-28210 Three-port digital thermostatic valve

or

K-28211 Four-port digital thermostatic valve

or










K-28212 Six-port digital thermostatic valve


Recommended Products/Accessories

K-28213 Remote on/off button for digital thermostatic valve

Available Colors/Finishes

Color tiles intended for reference only.

| Color | Code | Description |
|---|------|--------------------------------|
|  | SN | Vibrant® Polished Nickel |
|  | AF | Vibrant® French Gold |
|  | BN | Vibrant® Brushed Nickel |
|  | BV | Vibrant® Brushed Bronze |
|  | BL | Matte Black |
|  | 2MB | Vibrant® Brushed Moderne Brass |
|  | RGD | Vibrant Rose Gold |
|  | BGP | Vibrant Brushed Graphite |
|  | TT | Vibrant Titanium |



Technical Information

All product dimensions are nominal.

Spout:

Cable length: Data, 32 ft (9.8 m)

Max. Ambient temp: 120°F (48.9°C)

Notes

Install this product according to the installation instructions.